

TrueNet®

HighBand® Patch Cord – 1 or 2-pair to RJ45

Issue 1



Used for patching between HighBand modules and equipment with an RJ45 interface.

Provides 1-pair patching on HighBand 10, and 2-pair patching on HighBand 16 and 20.

Features:

- The 1 or 2-pair end of the patch cord has a locking feature to secure the patch cord to the module

Specifications

Environment for use:..... Indoors, in dry closed rooms
Operation temperature range: -10°C to + 60°C
Maximum relative humidity: ≤93% non-condensing
Insulation resistance: 100MΩ at 500VDC
Flammability rating of plastic housing: UL 94 V-0
No: of PCB insertion cycles: Typically 200
Plug material:..... Tough Thermoplastic Polymer
Safety: UL 1863

SPEC SHEET

Ordering Information

Description	Quantity	Colour	Product No.
HighBand Patch Cord, 1 or 2-pair to RJ45, 1m	Bag of 2	White	6451 2 080-11
HighBand Patch Cord, 1 or 2-pair to RJ45, 2m	Bag of 2	White	6451 2 080-21

adckrone.com/au • 1800 801 298 • helpdesk.au@adckrone.com



ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

6451 2 080-XX / Issue 1 © 2009 ADC Telecommunications, Inc. All Rights Reserved.