

TrueNet®

HighBand® 10 Test Cords

Issue 1



4-pair to RJ45 Test Cord



2-pair to RJ45 Test Cord

HighBand 10 Test cords used for either 4-pair or 2-pair testing on HighBand 10 modules. The RJ45 end allows connection to test equipment.

Specifications

Environment for use:..... Indoors, in dry closed rooms
 Operation temperature range: -10°C to + 60°C
 Maximum relative humidity: ≤93% non-condensing
 Insulation resistance: 100MΩ at 500VDC
 Flammability rating of plastic housing: UL 94 V-0
 No: of PCB insertion cycles: Typically 200
 Plug material:..... Tough Thermoplastic Polymer
 Safety: UL 1863

SPEC SHEET

Ordering Information

Description	Quantity	Colour	Product No.
HighBand 10 Test Cord, 4-pair to RJ45, 3m	Bag of 1	Blue	6451 2 099-30
HighBand 10 Test Cord, 2-pair to RJ45, 3m	Bag of 1	Blue	6451 2 100-30

adckrone.com/au • 1800 801 298 • helpdesk.au@adckrone.com



ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
 Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

6451 2 099 & 100-30 / Issue 1 © 2009 ADC Telecommunications, Inc. All Rights Reserved.