

TrueNet®

Category 3 1-pair Rear Facing Patch Cord

Issue 5



The 1-pair patch cord is used for patching 1-pair to 1-pair on HighBand 25 modules.

Applications include:

- Voice patching
- Pair testing
- Building management systems, 1-pair sensor or control plug-ins

Features:

- Category 3 performance
- Internal IDC/PCB wire termination
- Internal cable strain relief

Specifications

Environment for use:..... Indoors, in dry closed rooms
Operation temperature range: -10°C to + 60°C
Maximum relative humidity: ≤93% non-condensing
Insulation resistance: 100MΩ at 500VDC
Flammability rating of plastic housing: UL 94 V-0
No. of PCB insertion cycles: Typically 200
Plug Material: Tough Thermoplastic Polymer

SPEC SHEET

Ordering Information

Description	Quantity	Colour	Product No.
HighBand Patch Cord, 1-pair to 1-pair, Rear Facing, 1.2m	Bag of 1	White	6451 2 702-10
HighBand Patch Cord, 1-pair to 1-pair, Rear Facing, 2.1m	Bag of 1	White	6451 2 702-20
HighBand Patch Cord, 1-pair to 1-pair, Rear Facing, 3.0m	Bag of 1	White	6451 2 702-30
HighBand Patch Cord, 1-pair to 1-pair, Rear Facing, 4.5m	Bag of 1	White	6451 2 702-40

adckrone.com/au • 1800 801 298 • helpdesk.au@adckrone.com



ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

6451 2 702-XX / Issue 5 © 2009 ADC Telecommunications, Inc. All Rights Reserved.