

# TrueNet®

## Keystone RJ12 Outlet

Issue 4



For mounting into Keystone Mount applications; Keystone surface mount boxes, faceplates etc.

### Specifications

Environment for use: ..... Indoors, in closed rooms  
Operation temperature range: ..... -20°C to + 70°C  
Relative humidity: ..... ≤93% non-condensing  
RJ Socket, 6 positions, general specification: ..... FCC 68.500  
..... IEC 603-7  
Voltage/Current rating at 25°C ambient: ..... ≤150VAC at 2.5A max.  
Dielectric strength: ..... ≥1.5kVAC  
RJ Interface resistance: ..... ≤20mΩ  
Wire diameter range for solid & stranded copper conductors: ..... 0.40 – 0.65mm\* (26-22 AWG)  
Number of plug insertion cycles: ..... ≥1250  
Number of wire terminations (ADC KRONE Tool): ..... ≥200  
Number of wire terminations (110 Tool): ..... ≥100  
Flammability rating of plastic components: ..... UL 94 V-0  
ACA Compliant

\*If any conductors have been terminated, reversal to smaller conductors is no longer possible.

SPEC SHEET



[adckrone.com/au](http://adckrone.com/au) • 1800 801 298 • [helpdesk.au@adckrone.com](mailto:helpdesk.au@adckrone.com)

# TrueNet®

## Keystone RJ12 Outlet

### Ordering Information

Description	Quantity	Colour	Product No.
Keystone RJ12 Outlet	Bag of 10	Grey	6467 5 195-00
Keystone RJ12 Outlet	Bag of 10	Ivory	6467 5 195-10
Keystone RJ12 Outlet	Bag of 10	White	6467 5 195-20
Keystone RJ12 Outlet	Bag of 10	Electrical Ivory	6467 5 195-22
Keystone RJ12 Outlet	Bag of 10	Electrical Brown	6467 5 195-24
Keystone RJ12 Outlet	Bag of 10	Black	6467 5 195-30
Keystone RJ12 Outlet	Bag of 10	Blue	6467 5 195-40
Keystone RJ12 Outlet	Bag of 10	Red	6467 5 195-50
Keystone RJ12 Outlet	Bag of 10	Orange	6467 5 195-60
Keystone RJ12 Outlet	Bag of 10	Purple	6467 5 195-70
Keystone RJ12 Outlet	Bag of 10	Green	6467 5 195-80
Keystone RJ12 Outlet	Bag of 10	Yellow	6467 5 195-90

SPEC SHEET



#### [www.adckrone.com/au](http://www.adckrone.com/au)

AUSTRALIA 2 Hereford Street, Berkeley Vale NSW 2261  
Mailing Address: PO Box 335, Wyong NSW 2259, Australia  
Sales Support: 1800 801 298

#### [www.adckrone.com/nz](http://www.adckrone.com/nz)

NEW ZEALAND 2 Nevis Street, Petone, Wellington  
Mailing Address: PO Box 38-177, Wellington Mail Centre 6008, New Zealand  
Sales Support: 0800 657 663

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101  
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

6467 5 195-XX / Issue 4 © 2009 ADC Telecommunications, Inc. All Rights Reserved.