

TrueNet®

Sliding Rear Angled Fibre Patch Panel, 1RU

Issue 2



The sleek modern design of this fibre panel compliments the existing TrueNet range of patch panels and further enhances your cabling system or data centre. The superior, modular system is designed to meet Class II Laser Products as per AS/ACIF S008:2001 to keep you light years ahead of your cabling needs.

The panel is designed for the interconnection or cross-connection between campus backbone cabling, building backbone cabling, or horizontal cabling systems. The patch panel can be equipped for up to 48 ports in 1 rack unit depending on the type of adaptor plates or adaptor kits to be fitted.

Features:

- 12, 24 or 48-port in 1 rack unit
- Angled adaptor plates available for safety and improved patch cord and internal fibre management
- Internal tray extends past the face of the 19" rack via telescopic sliders for easy access to the internal fibre management system and through adaptors
- Hinged front cover to allow access to patch cords and adaptors when fitted
- Labelling on the front and rear surface of the hinged cover for port identification
- Optional second side mounting locations to allow the patch panel to be positioned further forward in the 19" rack
- Strain relief posts removable for ease of installation
- Provision to fit either a 24-position or a 48-position splice tray

SPEC SHEET



adckrone.com/au • 1800 801 298 • helpdesk.au@adckrone.com

TrueNet®

Sliding Rear Angled Fibre Patch Panel, 1RU

Specifications

Mechanical:

Interface: Accepts 12 to 24 SC & SC/APC, and 48 LC adaptors
 Depth: 385mm
 Height: 44mm / 1 rack unit
 Width: 19" rack mountable
 Internal tray 390mm
 Weight: 6.44kg

Environmental and Safety (patch panel only):

Safety Compliance: AS/NZS 2211.1, IEC 608 52-1 Safety of Laser Products
 Operating Temperature: -40°C + 60°C
 Storage Temperature: -40°C + 60°C

Ordering Information

Description	Quantity	Colour	Product No.
Sliding Rear Angled Fibre Patch Panel, 1RU	Box of 1	Dark grey	6877 1 001-10
Accessories:			
Optional Adaptor Plate Kits (without through adaptors):			
12-port SC/24-port LC	Box of 2	Dark grey	6877 2 014-00
24-port SC/48-port LC	Box of 2	Dark grey	6877 2 014-03
24-port SC Duplex	Box of 2	Dark grey	6877 2 014-05
Note : Adaptor plate 6877 2 014-03 is suitable for flangeless adaptors only			
24 position Splice Tray	Bag of 1	Black	FST-D-HS
48 position Splice Tray	Bag of 1	Black	FST-HS-48

SPEC SHEET



www.adckrone.com/au

AUSTRALIA 2 Hereford Street, Berkeley Vale NSW 2261
 Mailing Address: PO Box 335, Wyong NSW 2259, Australia
 Sales Support: 1800 801 298

www.adckrone.com/nz

NEW ZEALAND 2 Nevis Street, Petone, Wellington
 Mailing Address: PO Box 38-177, Wellington Mail Centre 6008, New Zealand
 Sales Support: 0800 657 663

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
 Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

6877 1 001-10 / Issue 2 © 2010 ADC Telecommunications, Inc. All Rights Reserved.