

TrueNet®

Plug-and-Play Cassettes



ADC KRONE's TrueNet® Fibre Panels (TFP) combine the unique features of vertical cable guides and our patented angle-left/angle right adapters, which offers bend radius protection, intuitive routing and easy connector access. Our TFP series can be ordered in one, two, or five rack-unit sizes to fit your unique needs. Designed for rack or cabinet mounting in the horizontal or equipment distribution area, the TFP's modularity, functionality and density make them ideal for mounting in close proximity to servers, switches, routers and SANs.

The TFP's functionality can be extended with its plug-and-play angled cassettes, which add up to 24-fibre terminations each for jumper management in SANs-rich environments. These cassettes snap into place effortlessly; and even come from the factory pre-labeled with simple installation instructions.

Features

- Eliminates the need for on-site fibre terminations, which means rapid deployments
- Incorporates angle left/angle right adapters to ensure proper bend radius
- Use the same 1, 2, and 5 rack unit standard TFP chassis, which simplifies ordering



TrueNet® plug-and-play angled cassettes in use

TECHNICAL DATA



Technical Assistance:
Europe & Middle East
+32 2 712 6542
euro.tac@adckrone.com
www.adckrone.com

South Africa
+27 11 466 3333
infos@adckrone.com

United Kingdom
0800 960236
contactuk@adckrone.com

ENVIRONMENTAL CHARACTERISTICS

Storage Temperature:	-40° to 70 °C
Operating Temperature:	0° to 70 °C
Installation Temperature:	0° to 70 °C

Ordering Information

Description	Catalogue Number
Termination only rack or cabinet mount panel, black	
1U empty panel, black; accommodates 2 modular adapter packs; T-handle latch close	TFP-1TT00-000B
2U empty panel, black; accommodates 4 modular adapter packs; T-handle latch close	TFP-2TT00-000B
5U empty panel, black; accommodates 12 modular adapter packs; T-handle latch close	TFP-5TT00-000B
Plug-and-Play Cassette Pairs	
12-fibre cassettes; 6 LC (aqua) multimode adapters; 50/125 fibre laser optimised to 300 meters	
Angle LEFT cassette	TFP-12MPLDQ2
Angle RIGHT cassette	TFP-12MPRDQ2
24-fibre cassettes; 12 LC (aqua) multimode adapters; 50/125 fibre laser optimised to 300 meters	
Angle LEFT cassette	TFP-24MPLDQ2
Angle RIGHT cassette	TFP-24MPRDQ2
12-fibre cassettes; 6 LC singlemode adapters; singlemode fibre	
Angle LEFT cassette	TFP-12MPLSQ5
Angle RIGHT cassette	TFP-12MPRSQ5
24-fibre cassettes; 12 LC singlemode adapters; singlemode fibre	
Angle LEFT cassette	TFP-24MPLSQ5
Angle RIGHT cassette	TFP-24MPRSQ5

TECHNICAL DATA



Web Site: www.adckrone.com/en

UK Office: ADC Communications (UK) Ltd., Runnings Road, Kingsditch Trading Estate, Cheltenham, Gloucestershire GL51 9NQ, United Kingdom • Phone: +44 (0) 1242 264 400 Fax: +44 (0) 1242 264 488 Email: contactuk@adckrone.com

South African Office: ADC Telecommunications (Africa) PTY Ltd., 16 Brand Hatch Close, Kyalami Business Park, Midrand, 1685 Johannesburg, South Africa • Phone: +27 11 466 3333 Fax: +27 11 466 3300 Email: infos@adckrone.com

EMEA Office: ADC GmbH, Beeskowdamm, 3-11, 14167 Berlin, Germany • Phone: +49 308 453 1818 Fax: +49 308 453 1703. For a listing of all ADC KRONE's global sales office locations, please refer to our web site.

Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC KRONE reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting ADC GmbH headquarters in Berlin. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents.

103942BE Oct 09 Revision © 2008, 2009 ADC Communications (UK) Ltd. All Rights Reserved